



Version	MARK	MODIFY	DATE
2.0	A	FPC	20100531
3.0		Action Area	20100820

Instruction:

- 1.Type:Film to Glass
- 2.Operating Voltage:≤10V
- 3.Response Time:≤10ms
- 4.Storage Temperature: -20~70 ℃
- 5.Operation Temperature/Humidity : ±10~60 ℃ / 20%~95%
- 6.Hitting Life:>1,000,000 Times ,250gf Force;
- 7.writing Life>100,000 Times 250gf Force;
- 8.Connect Material:FPC

- 9.Film Thickness:0.188mm
- 10.Glass Thickness:0.7mm
- 11.Light transmission>75%
- 12.Force100g or more
- 13.Linearity:≤1.5%
- 14.Insulation>20M Ω
- 15.Resistance: X:538~910 Ω;
Y:170~320 Ω
- 16.Surface Hardness:3H(pencil)

Touch-Pane-VTW4047A4

REVISIONS			
SCALE	1:1	MATERIAL	F/G
UNIT	mm	TOLERANCE	±0.3mm
DESIGN	Lucy	DATE	20100531
CHECK	peter?i	DATE	20100531
RELEASE	Victor	DATE	20100531

Version	3.0
NO.	1 of 1

Victor-Touch Technology Co., Ltd.
 0755-27248150 0755-27248039 www.victor-touch.com