


**Instruction:**

- 1.Type: Film to Glass
- 2.Operating Voltage: ≤10V
- 3.Response Time: ≤10ms
- 4.Storage Temperature: -20℃~+70℃
- 5.Operation Temperature/Humidity: -10℃~+60℃/ 20%~95%
- 6.Hitting Life: >1,000,000 Times ,250gf Force;
- 7.writing Life>100,000 Times250gf Force;
- 8.Connect Material:FPC

- 9.Film Thickness: 0.188mm
- 10.Glass Thickness: 0.7mm
- 11.Light transmission: ≥75%
- 12.Force: 100g or more
- 13.Linearity: ≤1.5%
- 14.Insulation: ≥20MΩ
- 15.Resistance: Y: 150Ω~380Ω  
X: 510Ω~1100Ω
- 16.Surface Hardness ≥3H(pencil)

Touch-Pane-VTW4062A5					
<b>REVISIONS</b>					
SCALE	1:1	MATERIAL	F/G	Version	1.0
UNIT	mm	TOLERANCE	±0.3mm	NO:	1 of 1
DESIGN	Lucy	DATE	20090912	 <b>深圳市纬拓光技术有限公司</b> Victor-touch Technology Co.,LTD.	
CHECK	Peter Li	DATE	20090912		
RELEASE	Victor	DATE	20090912		