



**Instruction:**

- 1.Type:Film to Glass
- 2.Operating Voltage:≤10V
- 3.Response Time:≤10ms
- 4.Storage Temperature: -20℃~+70℃
- 5.Operation Temperature/Humidity : -10℃~+60℃/ 20%~95%
- 6.Hitting Life:>1,000,000 Times ,250gf Force;
- 7.writing Life>100,000 Times 250gf Force;
- 8.Connect Material:FPC+PIN

- 9.Film Thickness:0.188mm
- 10.Glass Thickness:1.1mm
- 11.Light transmission: ≥78%
- 12.Force:100g or more
- 13.Linearity:≤1.5%
- 14.Insulation: ≥20MΩ
- 15.Resistance: X: 410Ω~700Ω  
Y: 220Ω~380Ω
- 16.Surface Hardness ≥3H(pencil)

Touch-Pane-VTW4084A0					
REVISIONS					
SCALE	1:1	MATERIAL	F/G	Version	1.0
UNIT	mm	TOLERANCE	±0.3m	NO.	1 of 1
DESIGN	Lucy	DATE	20090505	<b>深圳市维拓光电技术有限公司</b> <b>Victor-touch Technology Co.,LTD.</b>	
CHECK	Peter + LJ	DATE	20090505		
RELEASE	Victor	DATE	20090505		