



Instruction:

- 1.Type: Film to Glass
- 2.Operating Voltage: $\leq 10V$
- 3.Response Time: $\leq 10ms$
- 4.Storage Temperature: $-20^{\circ} \sim +70^{\circ}$
- 5.Operation Temperature/Humidity : $-10^{\circ} \sim +60^{\circ} / 20\% \sim 95\%$
- 6.Hitting Life: $> 1,000,000$ Times ,250gf Force;
- 7.writing Life $> 100,000$ Times 250gf Force;
- 8.Connect Material: FPC+PIN

- 9.Film Thickness: 0.188mm
- 10.Glass Thickness: 1.8mm
- 11.Light transmission: $\geq 78\%$
- 12.Force: 100g or more
- 13.Linearity: $\leq 1.5\%$
- 14.Insulation: $\geq 20M\Omega$
- 15.Resistance: Y: 230 Ω ~400 Ω
X: 380 Ω ~700 Ω
- 16.Surface Hardness $\geq 3H$ (pencil)

Touch-Pane-VTW4121A0

REVISIONS

SCALE	1:1	MATERIAL	F/G	Version	1.0
UNIT	mm	TOLERANCE	$\pm 0.3m$	NO.	1 of 1
DESIGN	Lucy	DATE	20090522	 深圳市锦拓光技术有限公司 Victor-Touch Technology Co., LTD.	
CHECK	Peter • L1	DATE	20090523		
RELEASE	Victor	DATE	20090523		