



**Instruction:**

- 1.Type:Film to Glass
- 2.Operating Voltage:≤10V
- 3.Response Time:≤10ms
- 4.Storage Temperature: -20℃~+70℃
- 5.Operation Temperature/Humidity : -10℃~+60℃/ 20%~95%
- 6.Hitting Life:>1,000,000 Times ,250gf Force;
- 7.writing Life>100,000 Times 250gf Force;
- 8.Connect Material:FPC+PIN

- 9.Film Thickness:0.188mm
- 10.Glass Thickness:1.8mm
- 11.Light transmission: ≥78%
- 12.Force:100g or more
- 13.Linearity: ≤5%
- 14.Insulation: ≥20MΩ
- 15.Resistance: 50Ω<PIN1, PIN2<280Ω  
50Ω<PIN2, PIN4<280Ω  
50Ω<PIN4, PIN6<280Ω  
50Ω<PIN6, PIN1<280Ω
- 16.Surface Hardness≥3H(pencil)

**Touch-Pane-VTW5156A0**

REVISIONS					
SCALE	1:1	MATERIAL	F/G	Version	1.0
UNIT	mm	TOLERANCE	±0.3m	NO.	1 of 1
DESIGN	Lucy	DATE	20100519	 <b>深圳市伟拓光电技术有限公司</b> Victor-Touch Technology Co., LTD. <small>020-2760-02000 020-2760-02000 www.victor-touch.com</small>	
CHECK	Peter • Li	DATE	20100519		
RELEASE	Victor	DATE	20100519		