



Instruction:

- 1.Type: Film to Glass
- 2.Operating Voltage: ≤10V
- 3.Response Time: ≤10ms
- 4.Storage Temperature: -20℃~+70℃
- 5.Operation Temperature/Humidity : -10℃~+60℃/ 20%~95%
- 6.Hitting Life: >1,000,000 Times ,250gf Force;
- 7.writing Life>100,000 Times 250gf Force;
- 8.Connect Material: FPC+PIN

- 9.Film Thickness: 0.188mm
- 10.Glass Thickness: 1.8mm
- 11.Light transmission: ≥78%
- 12.Force: 100g or more
- 13.Linearity: ≤5%
- 14.Insulation: ≥20MΩ
- 15.Resistance: 50Ω<PIN1, PIN2<280Ω
50Ω<PIN2, PIN4<280Ω
50Ω<PIN4, PIN5<280Ω
50Ω<PIN5, PIN1<280Ω
- 16.Surface Hardness ≥3H(pencil)

Touch-Pane-VTW5185A0

REVISIONS					
SCALE	1:1	MATERIAL	F/G	Version	1.0
UNIT	mm	TOLERANCE	±0.3m	NO.	1 of 1
DESIGN	Lany	DATE	20100528	深圳市维拓光技术有限公司 Victor-Touch Technology Co., LTD. TEL: +86-755-27662828 FAX: +86-755-27662828 www.victor-touch.com	
CHECK	Peter • LI	DATE	20100528		
RELEASE	Victor	DATE	20100528		