



**Instruction:**

- 1.Type:Film to Glass
- 2.Operating Voltage: ≤10V
- 3.Response Time: ≤10ms
- 4.Storage Temperature: -20℃~+70℃
- 5.Operation Temperature/Humidity : -10℃~+60℃/ 20%~95%
- 6.Hitting Life:>1,000,000 Times ,250gf Force;
- 7.writing Life>100,000 Times 250gf Force;
- 8.Connect Material:FPC+PIN

- 9.Film Thickness: 0.188mm
- 10.Glass Thickness: 1.8mm
- 11.Light transmission: ≥78%
- 12.Force: 100g or more
- 13.Linearity: ≤5%
- 14.Insulation: ≥20MΩ
- 15.Resistance: 50Ω < PIN1, PIN2 < 280Ω  
50Ω < PIN2, PIN4 < 280Ω  
50Ω < PIN4, PIN6 < 280Ω  
50Ω < PIN6, PIN1 < 280Ω
- 16.Surface Hardness ≥3H(pencil)

**Touch-Pane-VTW5215A0**

**REVISIONS**

SCALE	1:1	MATERIAL	F/G		Version	1.0
UNIT	mm	TOLERANCE	±0.3mm		NO.	1 of 1
DESIGN	Lucy	DATE	20110316			
CHECK	Peter • Li	DATE	20110316			
RELEASE	Victor	DATE	20110316			